



DRILLFORM

FORMING THE FUTURE OF DRILLING EQUIPMENT

BULLDOG 800

SERVICE RIG CATWALK



BULLDOG 800 FEATURES & BENEFITS

COST SAVINGS | Faster cycle times and a higher lift capacity

EASE OF USE | A simple setup, the BD800 features hydraulic kickers, indexers, a skate and self-leveling capabilities

RISK REDUCTION | No deck design increases personnel safety by reducing fall risk

EASE OF TRANSPORT | Unit is rigged up in minutes and designed to be moved via winch, truck or crane

DRILLFORM.COM | SALES@DRILLFORM.COM | +1 (403) 263 3133

BULLDOG 800

SERVICE RIG CATWALK

Hands-Free Tubular Handling for Service Rigs

The BD800 features hydraulic kickers, indexers, skate and self-levelling capabilities while increasing safety in pipe handling. A hydraulically folding ramp accommodates rig floor height of up to 6m with adjustable pipe racks for Range II and Range III tubulars.

The BD800 is rigged up in minutes and designed for transport via winch, crane or truck. The no deck design reduces the overall weight and increases personnel safety.

BULLDOG 800

SPECIFICATIONS

HYDRAULICS

Power Supply: Rig power 380, 480, 600 VAC Available
HPU: Drillform
Max Pressure: 3,000 psi / 210 Bar
Oil Reservoir: 46.7 Gallons / 177 Litres
Hydraulic Pump: Parker PVP48
Main Valve Bank: Parker L90
Secondary Valve Bank: Parker V20
Optional: Hydraulically adjustable telescoping V-door

ELECTRICAL

Motor: WEG W22
Ex Zoning: Motor is safety zoned & will be delivered to API 500
Power Connector: Appleton APC-60 Amp

TRANSPORTATION

Shipping Dimensions (L x W X H): 39½' x 7'x 8' / 12 m x 2.13 m x 2.44 m
Infield Dimensions (L x W x H): 39½' x 6'8" x 10'5" / 12 m x 2.03 m x 3.2 m
Ramp Width: 14" / 356 mm
Deck Height: 42" / 1,067 mm
Tongue Weight: 1,950 lbs
Transportation Weight: 16,000 lbs / 7.240 kg

HYDRAULIC PIPE RACKS

Pipe Rack Length: 15' 6" per side / 4.8 m per side
Max Capacity: 30,000 lbs per side / 13,600 kg per side
Adjustable Pipe Racks for Range II & Range III Tubulars

CAPACITY

Floor Height: 11.5' - 19.7' / 3.5 m - 6 m
OD: 2 ¾" to 7" / 60 mm - 178 mm
Range II & Range III
Weight: 1,500 lbs / 680 kg
Cycle time: 30 seconds

