



DRILLFORM

FORMING THE FUTURE OF DRILLING EQUIPMENT

BULLDOG 820

SERVICE RIG CATWALK



BULLDOG 820 FEATURES & BENEFITS

COST SAVINGS | Faster cycle times and a higher lift capacity

EASE OF USE | A simple setup, the BD820 features hydraulic kickers, indexers and skate

RISK REDUCTION | No deck design increases personnel safety by reducing fall risk

EASE OF TRANSPORT | Simple transition into transport mode with a pintle hitch for straightforward transportation

DRILLFORM.COM | SALES@DRILLFORM.COM | +1 (403) 263 3133

BULLDOG 820

SERVICE RIG CATWALK

Hands-Free Tubular Handling for Service Rigs

The BD820 features hydraulic kickers, indexers and skate while increasing safety in pipe handling. A telescoping ramp extends from 8' to 20' high and an extended pipe channel accommodates Range II and Range III tubulars. This towable catwalk includes a pintle hitch for easy towing and is available in towable and skid versions.

The BD820 offers a simple setup and transition into transport mode with rig up and rig down completed by two personnel. The no deck design reduces the overall weight of the trailer and increases personnel safety.



HYDRAULIC POWER UNIT

Independent Power Supply: 35 HP Diesel
HPU: Drillform
Max Pressure: 3,000 psi / 20,680 kPa
Diesel Fuel Tank: 26.4 Gallons / 100 Litres
Oil Reservoir: 46.7 Gallons / 177 Litres

TRANSPORTATION

Dimensions (LxWxH) : 39'8" x 7'4" x 9'2" / 12 m x 2.3 m x 2.8 m
Deck Height: 41³/₄" / 12.7 m
Tongue Weight: 1,950 lbs / 885 kg
Transportation Weight: 19,000 lbs / 8,600 kg
Tandem Axles

HYDRAULIC PIPE RACKS

Length: 16' 6" / 5.1 m
Max Capacity: 15,000 lbs each / 6,800 kg each
Adjustable Pipe Racks for RII & RIII Tubulars

TUBULAR CAPACITY

OD: 2 ³/₈" to 6" / 60 mm to 152 mm
Range II & Range III
Weight: 1,500 lbs / 680 kg

