



FEATURES & BENEFITS

SAFETY | Access to pipe handling pinch points and pipe movements is eliminated.

COST SAVINGS | Higher lift capacity, and accommodation of larger pipe diameters.

EASE OF MAINTENANCE | Modular and machined components contribute to ease and speed of maintenance.

OPERATIONAL ADVANTAGE | Center clearance for existing wellheads.

EASE OF USE | Modular design accommodates floor heights up to 47'. Integrated indexers, kickers and skate contribute to ease of pipehandling.

DRILLFORM.COM | INFO@DRILLFORM.COM | +1 (403) 263 3133

The Bulldog DC442 Drilling Catwalk boasts a 16,000 lb lift capacity and the ability to accommodate pipe diameters of up to 24". Offering a minimum floor height of 25' and a maximum height of 47', the DC442 is delivered with TechLink, allowing service personnel to remotely access the catwalk. The DC442 features independent and redundant controls located at the rear of the catwalk, while machined and modular components contribute to ease and speed of maintenance.



CATWALK DIMENSIONS

Width - Pipe Racks Closed: 96"/ 2.4 m

Deck Height: 36"/ 0.91 m Length: 84' / 25.6 m

Weight: 107,000 lbs / 48,500 kg Piperacks: 10' / 3 m per side

Piperack Capacity: 15,000 lbs / 6,800 kg per side

HYDRAULICS

Parker 145CC Remote P-Comp 3,000 PSI, 80 GPM Intake 5 Micro-Filtration Kidney Loop Continuous Cooling and Filtration L90 or PVG Valve System

OPERATIONAL DIMENSIONS

Max. Joint Length: 70'/ 21 m Max. Pipe Diameter: 24"/ 0.61 m Max. Lift Load: 16,000 lbs / 7,272 kg Floor Heights: 25' - 47' / 7.6 m - 14.3 m

Variable Ramp Angle: 45° - 50°

TRANSPORT DIMENSIONS

Length: 84' / 25.6 m Width: 10' / 3 m Height: 11' / 3.4 m

ADDITIONAL OPTIONS

Integrated Automated Pipe Tubs Hydraulic V-Door Setup Hydraulic X-Y Walking System Modular Ramp Heights

