

BULLDOG PCS PIPE CLEANING SYSTEM

FEATURES & BENEFITS

SAFETY | Mud is kept in the well rather than on the rig floor, preventing slips and other health hazards **TIME SAVINGS** | Pipe is cleaned as it comes out of the hole, contributing to less time rig cleaning **PRODUCT VERSATILITY** | Ability to be used to add chemicals to the wellbore rather than pit mixing **COST SAVINGS** | Clean up costs and time on the well are reduced



The Bulldog Pipe Cleaning System is a non-contact stripping tool designed to clean the entirety of the pipe string as it is removed from the well, a premier example of Drillform's commitment to bringing automated equipment to the drilling industry.

Specifications below are for 13%" BOP, the system will be available in all standard BOP sizes.

CAPACITIES

Through Bore Diameter: 11" & 13 %" / 280 mm & 346 mm

Dual Ring Stack Height: 131/2" / 343 mm

Load Capacity: 250T

Outer Diameter: 26" / 660 mm

Hose Connector Diameter: 1" / 25 mm

Connections per Ring: 2

CONTROLS & HMI

OMRON PLC Controls Wireless HMI Screen for Driller Operation Softstart for Blower and Pump Operations

Tank Level Gauges for Monitoring

Pump Stroke Counter for Continuous Kill Applications

BLOWER SIDE SPECIFICATIONS

Voltage: 480 VAC Horse Power: 40 HP

Blower CFM: 500 CFM Peak

Blower PSI: 15 PSI Peak / 103 kPa Peak

Wash Pump Pressure: 200 PSI Peak / 1,380 kPa Peak

Wash Pump Flow: 10 GPM Peak





